

DIMENSIONS FOR MICRO DRIVE SYSTEM

4 Panels High

FINISHED CEILING "A"	BEAM HEIGHT "B"	ACOUSTIC BARRIER "C"	POCKET DEPTH "D"	POCKET WIDTH "E"	PANEL HEIGHT "F"	WALL THICKNESS
2135 2160 2185	2750 2775 2800	2500 2525 2550	365 365 365	1440 1450 1465	595 602 608	300 300 300
2210 2235 2260	2825 2850 2875	2575 2600 2625	365 365 365	1480 1490 1505	614 621 627	300 300 300
2285 2310 2335	2900 2925 2950	2650 2675 2700	365 365 365	1515 1530 1540	633 640 646	300 300 300
2360 2390 2415	2975 3005 3030	2725 2755 2780	365 365 365	1555 1565 1580	653 659 665	300 300 300
2440 2465 2490	3055 3080 3105	2805 2830 2855	365 365 365	1590 1605 1615	672 678 684	300 300 300
2515 2540 2565	3130 3155 3180	2880 2905 2930	365 365 365	1630 1640 1655	691 697 703	300 300 300
2590 2615 2640	3205 3230 3255	2955 2980 3005	365 365 365	1665 1680 1690	710 716 722	300 300 300
2665 2690 2715 2740	3280 3305 3330 3355	3030 3055 3080 3105	365 365 365 365	1705 1720 1730 1745	729 735 741 748	300 300 300 300

Measurements are based on a C200x80.

Walls ranging in length from 3605mm long to 10980mm long.

Walls greater than 7315mm long - add an additional 25mm onto the beam height.

*** Beam heights indicated may vary with wall size and motor size.**

This table is not for construction purposes. Refer to shop drawings for final build to dimensions.