

## TYPICAL DIMENSIONS

CEILING HEIGHT "A"	*BEAM HEIGHT "B"	TOP OF POCKET "C"	POCKET HEIGHT "D"	POCKET WIDTH "E"	GRID HEIGHT "F"	NUMBER OF PANELS HIGH
2440	3405	3085	645	1105	487	6 Panels High
2745	3710	3390	645	1205	538	
3050	4015	3695	645	1305	589	
3350	4320	3995	645	1410	640	
3430	4395	4075	645	1435	653	
3455	4550	4225	770	1145	508	8 Panels High
3660	4750	4430	770	1195	533	
3960	5055	4730	770	1270	572	
4265	5360	5035	770	1350	610	
4570	5665	5340	770	1425	648	
4610	5705	5380	770	1435	653	
4625	5920	5555	930	1255	538	10 Panels High
4875	6175	5805	930	1305	564	
5185	6480	6115	930	1365	594	
5490	6810	6445	955	1435	627	
5740	7065	6700	960	1485	652	
5770	7215	6840	1070	1290	556	12 Panels High
5795	7240	6880	1085	1295	559	
6100	7545	7185	1085	1350	584	
6405	7850	7490	1085	1400	610	
6710	8155	7795	1085	1450	635	
7015	8460	8100	1085	1500	660	
7315	8765	8405	1090	1550	686	

\* Beam heights indicated may vary with wall size and motor size.

This table is not for construction purposes. Refer to shop drawings for final build to dimensions.